



SALE PRE OWNED

jeanneau Prestige 46 fly

275 000 € All Tax Included

## Description

Beautiful boat in excellent maintenance condition.

Version 3 cabins + 2 bathrooms + sailor cabin aft with private bathroom.

Many ordinary and extraordinary maintenance works carried out between 2018 and 2024.

List of works available on request.

Sales commission excluded.

Navigation equipment:

Rudder angle indicator, Electronic engine control, On-Board Computer, DSC vhf, Depth Sounder (Raymarine), GPS (Raymarine E120), Autopilot (ST6001), Plotter with GPS antenna.

Staging and technical:

Engine Alarm, Anchor (Bruce 12,5 kg + 50 mt. catena), Water pressure pump, 10 Batteries (motori + servizi + elica di prua + generatore), Battery charger (Quick), Deck Shower (con miscelatore c/f), Twin Steering (sul fly con strumentazione completa), Directional Spotlight (di profondità), Hydraulic Flaps (Bennett), Flaps Indicators, Anchor Chain Washdown, Courtesy Lights (Led), Gangway (Besenzoni), Platform (maggiorata), Automatic Bilge Pump, Manual Bilge Pump, Entry door, Teak Cockpit, Shorepower connector, Water harbor connector system, Electronic instrumentation repeater (sul fly), Rollbar (vetroresina sul fly per antenne), Electric Windlass, swimming ladder, cockpit table, Tender (chiglia

## Specifications

YEAR

2005

WIDTH

4.36

FUEL TANK CAPACITY

1530

CABINS

3

ENGINE MANUFACTURER

Cummins QSC 8.3 -  
500 HO

HORSE POWER

2 X 500 CV

LENGTH

14.55

DRAFT

1.20

GUESTS CRUISING

14

BATHROOMS

1

ENGINE HOURS

1150

### General

TYPE	BRAND	MODEL	GUESTS CRUISING
Motorboat	jeanneau	Prestige 46 fly	14
CURRENT LOCATION	Toscana		

### Dimensions / Performance

WEIGHT (T)	FUEL CAPACITY (L)	CRUISING SPEED (ND)	TOP SPEED (ND)
9999.99	1530	23	27

### Building / facilities

HULL MATERIAL	HULL COLOR	AMOUNT OF CABINS	BERTHS
Vetroresina	Bianco	3	6
BATHROOM(S)	1		

### Engine room

ENGINE	NUMBER OF ENGINES HORSE POWER (CV)	ENGINE HOURS	FUEL
Cummins QSC 8.3 - 500 HO	2 x 500	1150	Diesel
BOW THRUSTER			

### Electricity / air conditioning

---

ENGINE BATTERY

BATTERY  
CHARGER

GENERATOR

AIR CONDITIONING

HEATING SYSTEM

### Navigation equipment

---

GPS

AUTO PILOT

VHF

NAVIGATION COMPASS

SONAR

ANCHOR

FLYBRIDGE

### Galley / Laundry / Entertainment

---

MICROWAVE

FREEZER

FRIDGE

TV

### Deck equipment

---

DECK SHOWER

### Safety equipment / miscellaneous

---

LIFE  
RAFT

BILGE PUMP






















Cummins MerCruiser Diesel   
RELIABILITY THROUGH INNOVATION

### QSC6.3 Quantum Engine Series

ENGINE DIMENSIONS												
Length*	Wider		Height		Weight (Dry)							
mm	in	mm	in	mm	in	kg	lb					
1174	46.2	839	33.0	962	38.0	390	855					

\*Standard model construction. Height by tie-down. Length by fuel nozzle.

FUEL CONSUMPTION (2.7 PROP CURVE)												
Rating	QSC3-300 F1000				QSC3-300 H0				QSC3-300 H000			
rpm	3000	2600	2000	1800	3000	2600	2000	1800	3000	2600	2000	1800
HP	492	367	281	262	404	293	275	251	398	289	251	198
lph	105.4	83.6	70.4	64.2	115.1	82.4	66.6	63.7	104.7	80.4	68.4	51.7
lph	133	492	483	335	542	449	368	296	533	438	340	163
gph	33	36.8	30.7	17.8	38.4	32.6	17.6	13.8	38.9	22.6	17.6	13.8

FUEL CONSUMPTION (2.7 PROP CURVE)												
Rating	QSC3-300 F1000				QSC3-300 H0				QSC3-300 H000			
rpm	3000	2600	2000	1800	3000	2600	2000	1800	3000	2600	2000	1800
HP	368	296	224	181	368	296	224	181	361	323	236	198
lph	86.1	65.6	50.1	41.8	100.0	76.7	59.3	48.5	99.2	81.9	68.8	53.8
lph	483	387	314	243	493	387	314	243	484	438	343	263
gph	25.9	20.7	15.9	12.8	28.6	20.3	15.7	12.2	26.5	23.2	18.2	14.3

\*Reference data for 680, 550, and 500 hp ratings.

**Rating Definition:**  
Ratings are based on ISO 8666 conditions of 2300hPa (23.6 inHg) and 23°C (73°F) and 50% relative humidity. Propeller pitch varies according to the test power available after initial run-in time and is 10% of rated power. Please refer to manufacturer's literature for more information.

**High Output (HO) Quantum Engines Only:**  
Intended for use in variable load applications where full power is limited to one hour and of every eight hours of operation. The rating is for manufacturer's maximum operating condition that operates less than one hour per year.

**Intermittent Duty (INT):**  
Intended for use in variable load applications where full power is limited to ten times out of every eight hours of operation. The rating is for manufacturer's maximum operating condition that operates less than 1,000 hours per year.

**Maximum Demand (MD):**  
Intended for use in variable load applications where full power is limited to one hour out of every eight hours of operation. The rating is for maximum, clean and load representative operating condition that operates less than 500 hours per year.

**www.cummins.com**  
4001 Lakes Ave. #201  
Channahon, IL 61018  
815-426-1000  
800-441-4261 Fax 815-426-1000  
©2009 Cummins MerCruiser Diesel

Cummins MerCruiser Diesel  
RELIABILITY THROUGH INNOVATION



## QSC8.3 Quantum Engine Series

### POWER RATINGS

Rating	HO/GS	HO	HO/GS	HO/INT	HO	INT/HO
Metric hp	600*	550*	540	500*	500	490
bhp	593	542	533	493	493	484
kW	442	404	398	368	368	361
Rated rpm	3000	3000	2600	2600	2600	2500
Max Torque ft-lbs	1327	1327	1273	1300	1280	1265
Max Torque N-m	1799	1799	1726	1763	1735	1715
rpm	1800	1800	1600	1800	1800	1700

\* Preliminary data for 600, 550, and 500 hp ratings.

### ENGINE SPECIFICATIONS

Configuration	In-line 6-cylinder, 4-stroke diesel
Bore & Stroke	114 mm x 135 mm (4.49 in x 5.31 in)
Displacement	8.3 L (505 in <sup>3</sup> )
Aspiration	Turbocharged/Aftercooled
Rotation	Counterclockwise facing flywheel

### FEATURES AND BENEFITS

#### Engine Design

With its roots going back to the proven 6CTA8.3, the **QSC8.3** is providing a Quantum Leap in the marine industry by incorporating the latest diesel engine technology. A high pressure common rail fuel system virtually eliminates start up white smoke and black smoke, improves fuel economy and significantly reduces noise. The engine includes a new cylinder head with four valves per cylinder, which allows the engine to breathe easier for increased acceleration and torque. All QSC8.3 ratings use a wastegated turbocharger.

#### Fuel System:

Left and right engine mounted fuel filter

#### Lubrication System:

Left and right engine mounted lube filter  
Cast aluminum oil pan

**Electrical System:** 12-volt and 24-volt systems available

**Emissions:** EPA Tier 2, IMO and RCD compliant

**Cooling System:** Sea water heat exchanger cooling system with electronic low coolant water level alarm

### AVAILABLE ACCESSORIES

**Air Intake System:** Light duty or serviceable type air cleaner

**Engine Controls:** C-Cruise Package (engine synchronization, slow idle, cruise 1 and 2, RPM +/-), back-up throttles, electronic throttle and shift

**Instrumentation:** SmartCraft® digital displays and/or analog gauges provide data on engine speed, oil pressure and engine load.

**Vessel System Integration:** SmartCraft monitors fluid level, vessel range, depth, vessel speed, rudder position, temperatures and more.

